

| ROLLANT  |       | 375 RC UNIWRAp | 375 RC     | 374 RC     | 374 RF     |
|--|-------|----------------|------------|------------|------------|
| <b>Hitching</b>  |       |                |            |            |            |
| PTO shaft speed  | rpm   | 1000           | 1000       | 1000       | 1000       |
| Power requirement  | kW/hp | 88/120         | 68/92      | 68/92      | 68/92      |
| Drive chains   |       | Heavy duty     | Heavy duty | Heavy duty | Heavy duty |
| <b>Hydraulic connection</b>  |       |                |            |            |            |
| One-way spool valve for pick-up lift and dual-acting spool valve for tailgate rams |       | –              | ●          | ●          | ●          |
| Single-acting spool valve and open return line                                     |       | ●              | –          | –          | –          |
| <b>Pick-up</b>   |       |                |            |            |            |
| Width  | m     | 2.10           | 2.10       | 2.10       | 2.10       |
| DIN raking width   | m     | 1.90           | 1.90       | 1.90       | 1.90       |
| Roller crop press  |       | ○              | ○          | ○          | ○          |
| Oscillating pick-up castor guide wheels  |       | ●              | ●          | ●          | ●          |
| <b>Crop feed</b>   |       |                |            |            |            |
| Heavy-duty ROTO CUT cutting rotor  |       | ●              | ●          | ●          | –          |
| Number of knives   |       | 16             | 16         | 16         | –          |
| Lowerable PRO cutting floor  |       | ●              | ●          | ●          | –          |
| <b>Bale chamber</b>  |       |                |            |            |            |
| Number of compaction rollers   |       | 16             | 16         | 16         | 16         |
| Automatic chain lubrication  |       | ●              | ●          | ●          | ●          |
| Automatic central lubrication for baler bearings                                   |       | ○              | ○          | ○          | ○          |
| Bale ejector   |       | –              | ●          | ●          | ●          |
| <b>Bale chamber dimensions</b>   |       |                |            |            |            |
| Width  | m     | 1.20           | 1.20       | 1.20       | 1.20       |
| Diameter   | m     | 1.25           | 1.25       | 1.25       | 1.25       |
| <b>Operation</b>   |       |                |            |            |            |
| COMMUNICATOR II  |       | ●              | –          | –          | –          |
| CLAAS MEDIUM TERMINAL II (wrapper)   |       | ●              | –          | –          | –          |
| OPERATOR   |       | –              | ●          | ●          | ●          |
| ISOBUS cable   |       | ●              | ●          | ●          | ●          |
| <b>Wrapping and tying</b>  |       |                |            |            |            |
| Net wrapping   |       | ●              | ●          | ●          | ●          |
| Twine tying  |       | ●              | ●          | ●          | ●          |
| <b>Wrapper</b>   |       |                |            |            |            |
| Film stretcher   | mm    | 2 x 750        | –          | –          | –          |
| Film capacity  |       | 12 rolls       | –          | –          | –          |
| Overlap, configurable  | %     | 52             | –          | –          | –          |
| Pre-stretching   | %     | 67 (82 ○)      | –          | –          | –          |
| <b>Tyres</b>   |       |                |            |            |            |
| 15.0/55-17 10 PR   |       | –              | ●          | ●          | ●          |
| 19.0/45-17 10 PR   |       | –              | ○          | ○          | ○          |
| 500/45-22.5 12 PR  |       | –              | ○          | ○          | ○          |
| 560/45-22.5 12 PR  |       | ●              | –          | –          | –          |
| Air brakes   |       | ●              | ○          | ○          | ○          |
| <b>Overall dimensions</b>  |       |                |            |            |            |
| Length   | mm    | 6690           | 4720       | 4720       | 4720       |
| Width  | mm    | 2980           | 2330–2770  | 2330–2770  | 2330–2770  |
| Height   | mm    | 2830           | 2310       | 2310       | 2310       |
| Weight   | kg    | 4700           | 2750       | 2750       | 2750       |

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

| ROLLANT  |       | 455 RC UNIWRAP     | 455 RC             | 454 RC UNIWRAP     | 454 RC             |
|--|-------|--------------------|--------------------|--------------------|--------------------|
| <b>Hitching</b>                                    |       |                    |                    |                    |                    |
| PTO shaft speed                                    | rpm   | 1000               | 1000               | 1000               | 1000               |
| Power requirement                                  | kW/hp | 107/145            | 74/100             | 107/145            | 74/100             |
| Ball hitch   |       | ○                  | ○                  | ○                  | ○                  |
| Drive chains                                       |       | Heavy duty         | Heavy duty         | Heavy duty         | Heavy duty         |
| <b>Hydraulic connection</b>                        |       |                    |                    |                    |                    |
| 2 x single-acting spool valve and open return line |       | ●                  | ●                  | ●                  | ●                  |
| <b>Pick-up</b>                                     |       |                    |                    |                    |                    |
| Width  | m     | 2.10               | 2.10               | 2.10               | 2.10               |
| DIN raking width                                   | m     | 1.90               | 1.90               | 1.90               | 1.90               |
| Roller crop press                                  |       | ○                  | ○                  | ○                  | ○                  |
| Oscillating pick-up castor guide wheels            |       | ●                  | ●                  | ●                  | ●                  |
| <b>Crop feed</b>                                   |       |                    |                    |                    |                    |
| Heavy-duty ROTO CUT cutting rotor                  |       | ●                  | ●                  | ●                  | ●                  |
| Number of knives                                   |       | 25 (0, 12, 13, 25) | 25 (0, 12, 13, 25) | 25 (0, 12, 13, 25) | 25 (0, 12, 13, 25) |
| HD knives  |       | ○                  | ○                  | ○                  | ○                  |
| Blanked-off knives                                 |       | ○                  | ○                  | ○                  | ○                  |
| Lowerable PRO cutting floor                        |       | ●                  | ●                  | ●                  | ●                  |
| <b>Bale chamber</b>                                |       |                    |                    |                    |                    |
| Number of compaction rollers                       |       | 16                 | 16                 | 16                 | 16                 |
| Automatic chain lubrication                        |       | ●                  | ●                  | ●                  | ●                  |
| Automatic central lubrication for baler bearings   |       | ○                  | ○                  | ○                  | ○                  |
| Bale ejector                                       |       | –                  | ●                  | –                  | ●                  |
| <b>Bale chamber dimensions</b>                     |       |                    |                    |                    |                    |
| Width  | m     | 1.20               | 1.20               | 1.20               | 1.20               |
| Diameter   | m     | 1.25–1.35          | 1.25–1.35          | 1.25–1.35          | 1.25–1.35          |
| <b>Operation</b>                                   |       |                    |                    |                    |                    |
| COMMUNICATOR II                                    |       | ●                  | ●                  | ●                  | ●                  |
| CLAAS MEDIUM TERMINAL II (wrapper)                 |       | ●                  | –                  | ●                  | –                  |
| OPERATOR   |       | –                  | –                  | –                  | –                  |
| ISOBUS cable                                       |       | ●                  | ●                  | ●                  | ●                  |
| <b>Wrapping and tying</b>                          |       |                    |                    |                    |                    |
| Net wrapping                                       |       | ●                  | ●                  | ●                  | ●                  |
| Twine tying  |       | –                  | –                  | –                  | –                  |
| <b>Wrapper</b>                                     |       |                    |                    |                    |                    |
| Film stretcher                                     | mm    | 2 x 750            | –                  | 2 x 750            | –                  |
| Film capacity                                      |       | 14 rolls           | –                  | 14 rolls           | –                  |
| Overlap, configurable                              | %     | 52                 | –                  | 52                 | –                  |
| Pre-stretching                                     | %     | 67 (82 ○)          | –                  | 67 (82 ○)          | –                  |
| Slope equipment                                    |       | ○                  | –                  | –                  | –                  |
| <b>Tyres</b>                                       |       |                    |                    |                    |                    |
| 15.0/55-17 10 PR                                   |       | –                  | ●                  | –                  | ●                  |
| 19.0/45-17 10 PR                                   |       | –                  | ○                  | –                  | ○                  |
| 550/60-22.5  |       | ●                  | –                  | ●                  | –                  |
| 560/45-22.5 16 PR                                  |       | –                  | ○                  | –                  | ○                  |
| 620/55 R 26.5                                      |       | ○                  | –                  | ○                  | –                  |
| Air brakes   |       | ●                  | ○                  | ●                  | ○                  |
| <b>Overall dimensions</b>                          |       |                    |                    |                    |                    |
| Length   | m     | 6990               | 4250               | 6990               | 4250               |
| Width  | m     | 2955               | 2955               | 2955               | 2955               |
| Height   | m     | 3250               | 3250               | 3250               | 3250               |
| Weight   | kg    | 5800               | 3150               | 5800               | 3150               |
| <b>Options</b>                                     |       |                    |                    |                    |                    |
| Work lights  |       | ○                  | ○                  | ○                  | ○                  |
| Bale twister                                       |       | ○                  | ○                  | ○                  | ○                  |
| Load sensing                                       |       | ○                  | ○                  | ○                  | ○                  |