

| VARIANT | | 485 RC PRO | 465 RC PRO | 480 RF/RC | 460 RF/RC | 470 RF | 450 RF |
|---|-------|------------------------|------------------------|-------------------------|-------------------------|--------------|--------------|
| Hitching | | | | | | | |
| PTO shaft speed | rpm | 1000/540 | 1000 (○) /540 | 540 or 1000 | 540 or 1000 | 540 | 540 |
| Power requirement | kW/hp | 75/102 | 75/102 | 75/102 | 75/102 | 68/92 | 68/92 |
| Main drive and drive chains | | Heavy Duty, 1 ¼" | Heavy Duty, 1 ¼" | Standard, 1" | Standard, 1" | Standard, 1" | Standard, 1" |
| Central chain lubrication | | ● | ● | ● | ● | ● | ● |
| Central lubrication system | | ○ | ○ | ○ | ○ | – | – |
| Ball hitch | | ○ | ○ | ○ | ○ | – | – |
| Hydraulic connection | | | | | | | |
| Single-acting spool valve for pick-up lift | | ● | ● | ● | ● | ● | ● |
| Dual-acting spool valve for tailgate rams | | ● | ● | ● | ● | ● | ● |
| Additional dual-acting spool valve for PRO cutting floor | | ● | ● | ● | ● | – | – |
| Pick-up | | | | | | | |
| Width | m | 2.10 | 2.35 (○) | 2.10 | 2.35 (○) | 2.10 | 2.10 |
| DIN pick-up width | m | 1.90 | 2.15 (○) | 1.90 | 2.15 (○) | 1.90 | 1.90 |
| Ground-contour following with two oscillating castor guide wheels | | ● | ● | ● | ● | ○ | ○ |
| Roller crop press | | ○ | ○ | ○ | ○ | ○ | ○ |
| Double-roller crop press | | ○ | ○ | ○ | ○ | – | – |
| Crop feed | | | | | | | |
| Forced feed with | | Heavy Duty ROTO CUT | Heavy Duty ROTO CUT | ROTO FEED / ROTO CUT | ROTO FEED / ROTO CUT | ROTO FEED | ROTO FEED |
| Number of knives (with ROTO CUT) | | 14 | 14 | 14 | 14 | – | – |
| Hydraulically lowerable PRO cutting floor | | ○ | ○ | ○ | ○ | – | – |
| Variable baling chamber | | | | | | | |
| High-strength endless belts | Qty. | 4 | 4 | 4 | 4 | 4 | 4 |
| Belt speed | m/s | 3 | 3 | 2.9 | 2.9 | 2.9 | 2.9 |
| Soft-core device, pressure and diameter adjustable | | ● | ● | ● | ● | ● | ● |
| Supplementary belt drive | | ● | ● | ● | ● | – | – |
| Moisture sensor | | ○ | ○ | ○ | ○ | – | – |
| Heavy Duty concept | | ● | ● | – | – | – | – |
| Bale chamber dimensions | | | | | | | |
| Width | m | 1.20 | 1.20 | 1.20 | 1.20 | 1.20 | 1.20 |
| Diameter | m | 0.90–1.80 | 0.90–1.55 | 0.90–1.80 | 0.90–1.55 | 0.90–1.80 | 0.90–1.55 |
| Operation | | | | | | | |
| OPERATOR | | ● | ● | ● | ● | ● | ● |
| COMMUNICATOR II | | ○ | ○ | ○ | ○ | ○ | ○ |
| ISOBUS cables | | ○ | ○ | ○ | ○ | ○ | ○ |

| VARIANT | | 485 RC PRO | 465 RC PRO | 480 RF/RC | 460 RF/RC | 470 RF | 450 RF |
|--|----|-------------|-------------|-------------|-------------|-------------|-------------|
| Wrapping | | | | | | | |
| NEW guiding plate | | ● | ● | ● | ● | ● | ● |
| Net wrapping with automatic start | | ● | ● | ● | ● | ● | ● |
| Number of net turns, selectable | | 9 settings | 9 settings | 9 settings | 9 settings | 9 settings | 9 settings |
| Dual twine wrapping with automatic wrapping start | | ○ | ○ | ○ | ○ | ● | ● |
| CLAAS Covered net wrapping | | ○ | ○ | ○ | ○ | ○ | ○ |
| CLAAS Covered XW net wrapping | | ○ | ○ | ○ | ○ | ○ | ○ |
| Number of twine turns, selectable | | 10 settings | 10 settings | 10 settings | 10 settings | 10 settings | 10 settings |
| Tyres | | | | | | | |
| 11.5/80 15.3 10PR | | – | – | – | – | ● | ● |
| 15.0/55 R 17 | | ● | ● | ● | ● | ○ | ○ |
| 19.0/45 R 17 | | ○ | ○ | ○ | ○ | ○ | ○ |
| 500/50 17 F+ | | ○ | ○ | ○ | ○ | – | – |
| Pick-up oscillating castor guide wheels 16/6.50-8 10PR | | ● | ● | ● | ● | ● | ● |
| Air brakes | | ○ | ○ | ○ | ○ | – | – |
| Dimensions and weights | | | | | | | |
| Length with bale ramp | m | 4.68 | 4.68 | 4.68 | 4.68 | 4.68 | 4.68 |
| Width with 15.0/55 R 17 tyres | m | 2.49 | 2.49 | 2.49 | 2.49 | 2.49 | 2.49 |
| Width with 19.0/45 R 17 tyres | m | 2.66 | 2.66 | 2.66 | 2.66 | 2.66 | 2.66 |
| Width with 500/50 17 F+ tyres | m | 2.67 | 2.67 | 2.67 | 2.67 | – | – |
| Height | m | 2.99–3.03 | 2.79–2.83 | 2.99–3.03 | 2.79–2.83 | 2.99–3.03 | 2.99–3.03 |
| Weight | kg | 3730 | 3530 | 3650 | 3400 | 3310 | 3170 |



15.0/55-17 10PR 19.0/45-17 10PR 500/50-17 F+

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

● Standard ○ Optional – Unavailable