

**PREMIUM LINE for ORBIS**

Part number	Description	Remarks
00 0383 148 0	Scraper, large knife disc, anti-clockwise	For ORBIS 900 / 750 / 600 / 450
00 0383 147 0	Scraper, large knife disc, anti-clockwise	For ORBIS 900 / 750 / 600 / 450
00 0498 380 0	Wear plate, sliding skid, large	For ORBIS 900 / 750 / 600 / 450
00 0499 006 0	Wear plate under knife disc	For ORBIS 900 / 750 / 600
00 0383 288 0	Intake drum, upper right	For ORBIS 900 / 750 / 600
00 0383 286 0	Intake drum, lower right	For ORBIS 900 / 750 / 600
00 0383 287 0	Intake drum, upper left	For ORBIS 900 / 750 / 600
00 0383 285 0	Intake drum, lower left	For ORBIS 900 / 750 / 600
00 0498 382 0	Wear plate, sliding skid, small	For ORBIS 900 / 750 / 600
00 0383 145 0	Scraper, small knife disc	For ORBIS 900 / 750 / 600
00 1319 479 0	Steel guide strip, centre left lower	For ORBIS 900 / 750
00 1319 480 0	Steel guide strip, centre left upper	For ORBIS 900 / 750
00 1319 835 0	Steel guide strip, small disc	For ORBIS 900 / 750
00 1319 481 0	Steel guide strip, centre right upper	For ORBIS 900 / 750
00 1319 487 0	Steel guide strip, centre left upper	For ORBIS 600 / 450
00 1319 485 0	Steel guide strip, centre left lower	For ORBIS 600 / 450
00 1319 825 0	Protection under ORBIS for drive, centre	For ORBIS 600 / 450
00 1319 486 0	Steel guide strip, centre right upper	For ORBIS 600 / 450
00 1319 669 0	Steel guide strip, outer	For ORBIS 750

**PREMIUM LINE for DIRECT DISC**

Part number	Description	Remarks
00 0905 014 0	Mowing disc for bolt-on knives	For DIRECT DISC 520
00 0137 448 0	Mowing disc for quick knife change system	For DIRECT DISC 610 / 520

**Compatibility of front attachments with JAGUAR**

	PICK UP 380 / 300	DIRECT DISC 610 / 520 NEW: 600 / 500	ORBIS 900	ORBIS 750	ORBIS 600 SD / 600	ORBIS 450	RU 450	Six-row CONSPEED maize picker with adapter
<b>JAGUAR</b>								
900 series	○ / ○	○ / ○	○	○	○ / ○	○	○	○
800 series	○ / ○	- / ○	-	○	○ / ○	○	○	○

**PICK UP front attachments**

PICK UP		380	300	300 HD
Working width	mm	3800	3000	3000
Transport width	mm	3970	3000	3000
Length	mm	1500	1500	1450
Height	mm	1400	1400	1300
Weight	kg	1500	1200	970

**Direct cutterbars**

DIRECT DISC		610	520	NEW: 600	NEW: 500
Working width	mm	5950	5125	5959	5132
Transport length on trailer	mm	10900	10000	10900	10000
Length	mm	2350	2350	2205	2205
Height	mm	1730	1730	1750	1750
Weight	kg	2700	2600	2900	2700

**Maize front attachments**

ORBIS		900	750	600 SD	600	450	RU 450
Working width	mm	9170	7600	6110	6150	4750	4500
Transport width	mm	3290	3000	2950	3000	3000	3000
Length	mm	2450	2450	2700	2350	2400	2900
Height	mm	1425	1425	2330	1350	1500	2100
Weight	kg	4000	3300	2830	2700	2255	2300

**ORBIS 900 / 750 with transport system: wheelbase to JAGUAR**

JAGUAR		Distance from centre of axle of ORBIS transport system to centre of JAGUAR drive axle
900	mm	1300
800	mm	1480

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual. All technical specifications relating to engines are based on the European emission regulation standards: Stage. Any reference to the Tier standards in this document is intended solely for information purposes and ease of understanding. It does not imply approval for regions in which emissions are regulated by Tier.